

CONCRETE FILLED BARE PANELS

AFS KIT MODEL: AKF15B

PANEL MODEL: RPF15B

- QUIET AND STRONG
- CARPET READY
- IN STOCK

FEATURES

- Full hard cold rolled steel top sheet
- Painted finish
- Cornerlock Holes
- Welded assembly at domes and perimeter
- Cementitious core material
- Draw quality steel bottom pan with structural dome design

GENERAL SPECIFICATIONS


- Panel size: 24" x 24"
- Kit weight: 12 lbs./ft bare.
- Panel weight: 40
- All steel welded construction filled internally with a cementitious core material.
- Protected from corrosion by an epoxy paint finish.
- Class A flame spread rating.
- Non-combustible material.

UNDERSTRUCTURE

- Corner Locking pedestals
- Available in heights from 6" to 36"


COVERING

- Bare, no surface covering



TOP VIEW

- Draw quality steel bottom pan with structural dome design
- Welded assembly at domes and perimeter
- Cementitious core material
- Painted finish
- Full hard cold rolled steel top sheet
- Cornerlock Hole



CORNER DETAIL



CROSS SECTION

- 1.32" deep at corners

SYSTEM PERFORMANCE RATINGS*			
DESIGN LOAD	UNIFORM LOAD	ULTIMATE LOAD	IMPACT LOAD
1500 lbs	450 lbs	3750 lbs	150 lbs
ROLLING LOAD		WARRANTY	
10 PASSES 1250 lbs	10,000 PASSES 1000 lbs	2 Years	

*Per CISCA Recommendations, Minimum