


GENERAL NOTES:

- 1) MATERIAL TO BE HOT DIPPED, PRE-GALVANIZED STEEL, TO AVOID THE FORMATION OF ZINC WHISKERS.
- 2) DIMENSIONAL TOLERANCES
 - A) LENGTH +/- 1/16"
 - B) WIDTH +/- 1/16"
 - C) SLOT LOCATION +/- 1/32"
 - D) ALL ANGLES TO BE 90 +/- 2 DEG.
- 3) MATERIAL THICKNESS (NOM) 18 GAGE

| COMPONENT LIST | | | |
|------------------------|-------------|------------|-------------------------|
| DIM. "L" | PART NUMBER | MAKE FROM | DESCRIPTION |
| 2" | | 476000 025 | CO SC GALV 0576 X 4.094 |
| 2-1/2" | | 476000 025 | CO SC GALV 0576 X 4.094 |
| 3" | | 476000 025 | CO SC GALV 0576 X 4.094 |
| 4" | | 476000 025 | CO SC GALV 0576 X 4.094 |
| 5" | | 476000 025 | CO SC GALV 0576 X 4.094 |
| 6" | | 476000 025 | CO SC GALV 0576 X 4.094 |
| 8" | | 476000 025 | CO SC GALV 0576 X 4.094 |
| 9" | | 476000 025 | CO SC GALV 0576 X 4.094 |
| 10" | | 476000 025 | CO SC GALV 0576 X 4.094 |
| 11" | | 476000 025 | CO SC GALV 0576 X 4.094 |
| 12" | | 476000 025 | CO SC GALV 0576 X 4.094 |
| 14" | | 476000 025 | CO SC GALV 0576 X 4.094 |
| 16" | | 476000 025 | CO SC GALV 0576 X 4.094 |
| 18" | | 476000 025 | CO SC GALV 0576 X 4.094 |
| 20" | | 476000 025 | CO SC GALV 0576 X 4.094 |
| 21" | | 476000 025 | CO SC GALV 0576 X 4.094 |
| 24" | | 476000 025 | CO SC GALV 0576 X 4.094 |
| 25" | | 476000 025 | CO SC GALV 0576 X 4.094 |
| 26" | | 476000 025 | CO SC GALV 0576 X 4.094 |
| 29" | | 476000 025 | CO SC GALV 0576 X 4.094 |
| OTHER LENGTH AVAILABLE | | | |

| | | | | | | | | | |
|---|------|--------|--------|--|-----------------------------|--|---|--------|----------------------------|
| UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. | | | | | DEBUR AND BREAK SHARP EDGES | |  985 898 0880 | | |
| REVISION | NAME | CHANGE | DATE | | | | | FILE | FLOORFLEX VERTICAL SUPPORT |
| A | AF | | 5-6-10 | | | | | DWG NO | VS2 - 29 |
| | | | | | MATERIAL: | | | | |
| | | | | | WEIGHT: | | SCALE: 1:1 | | |
| | | | | | | | SHEET 1 OF 1 | | |