



**AccessFloorSystems.com**  
PO Box 1148, Abita Springs, LA 70420  
985.898.0880, 985.892.8535 Fax  
[www.accessfloorsystems.com](http://www.accessfloorsystems.com)

01/29/20

Spec number 09 69 33 Low- Profile Access Floor Project

Criteria:	Netfloor USA ECO 40mm
Fixed Height	Yes
System Height	Eco 40 (1.6")
Panel Dims.	20.07" x 20.7"
Module Dims.	600mm (~2')
System Weight	2.56 lbs per psf
Panel Construction	Fire retardant, recycled polypropylene
Base Connector	6.65" x 6.65" x 0.59", recycled polycarbonate plus ABS
Central Cap	5.91" x 5.91" x 0.09" steel with reinforced ribs, corrosion resistance electroplated
Flank Cap	8.78" x 4.72" x 0.09" Steel reinforced ribs, electroplated
Sound Attenuation Blanket	0.08" thick IXPE
Test Results	
Concentrated load	2,000 lbs / 20" x 20"
Concentrated load / 1" X 1" (AT 0.1" deflection)	400 psi
Uniform Load / 0.06" Maximum deflexion	600 psf
Fire Protection	
Flame Spread 25 or less/ Non Combustible	25 (Meet BS476 part 4 ASTM E-84 class 1) / Comply
Smoke Index	Less than 50
Warranty	