

PEDESTAL FOR BOLTED STEEL & CONCRETE FILLED SYSTEMS

AFS KIT MODEL: PASCF

DESCRIPTION

1. 11 gauge galvanized Steel Head
2. Stud 3/4" - 10 UNC
3. Nut with vibration proof locking device
4. Tube 7/8" square x 16 gauge
5. Base plate 4" x 4" x 8 gauge
6. Fillet Weld

PEDESTAL SPECIFICATIONS

Pedestal Specifications

- Assembly up to 36" FFH shall provide a 6000 pound axial load without permanent deformation
- Assembly shall provide 2" total adjustment
- Electro-zinc free pedestal components and fasteners

Pedestal Head

- 11 gauge die formed galvanized steel pedestal head
- 3" x 3" pedestal head
- 3/4" steel stud - 10 UNC
- Stringers shall be attached with 1/4" - 20 flat head screws
- Adjustment nut to be 3/4" with corrosion resistant coating
- Studs offer anti-rotation feature when engaged with the pedestal base assembly

Pedestal Base

- 4" x 4" x 8 gauge hot dipped galvanized steel
- Tube size is 7/8" square x 16 gauge
- 4 ea. 7/16" diameter holes for mechanical fastening applications (non-standard)

Stringer

- Heavy duty roll formed steel stringer will withstand 450 pound mid span load
- Galvanized to prevent corrosion
- Stringer is 23" Long x 1 1/4" High x 3/4" Wide
- Used in a 2' grid pattern

Perimeter

- Perimeter pedestal shall provide support for panels around columns at walls curbs and facia

